

TABLE OF CONTENTS

1 STRUCTURAL ELEMENTS

1.1	Introduction	1 - 1
1.2	Reinforcement	1 - 3
1.2.1	Local Reinforcement at Joints (block struct reinforce Command)	1 - 3
1.2.1.1	Axial Behavior	1 - 4
1.2.1.2	Shear Behavior	1 - 5
1.2.1.3	Numerical Formulation	1 - 7
1.2.1.4	Estimation of Active Length	1 - 12
1.2.1.5	Local Reinforcement Properties	1 - 12
1.2.1.6	Summary of Commands Associated with Local Reinforcement Elements	1 - 13
1.2.1.7	Example Application – Reinforced Slope	1 - 15
1.2.2	Global Shearing-Resistant Reinforcement (block struct cable Command)	1 - 18
1.2.2.1	Axial Behavior	1 - 19
1.2.2.2	Shear Behavior of Grout Annulus	1 - 20
1.2.2.3	Normal Behavior at Grout Interface	1 - 22
1.2.2.4	Cable Element Properties	1 - 23
1.2.2.5	Pretensioning Cable Elements	1 - 26
1.2.2.6	Estimating the Maximum Length for Cable Element Segments	1 - 27
1.2.2.7	Connecting Cable Elements to Beam Elements and to Other Cable Elements	1 - 27
1.2.2.8	Summary of Commands Associated with Cable Elements	1 - 27
1.2.2.9	Example Application – Pull-Test for a Grouted Cable Anchor	1 - 29
1.2.3	Global Shearing- and Bending-Resistant Reinforcement (block struct rock-bolt Command)	1 - 33
1.2.3.1	Behavior of Rockbolt Segments	1 - 34
1.2.3.2	Behavior of Shear Coupling Springs	1 - 34
1.2.3.3	Behavior of Normal Coupling Springs	1 - 36
1.2.3.4	Rockbolt-Element Properties	1 - 38
1.2.3.5	Commands Associated with Rockbolt Elements	1 - 39
1.2.3.6	Example Application – Rockbolt Pullout Tests	1 - 42
1.2.3.7	Example Application – Rockbolt Shear Tests	1 - 51

1.3	Surface Support	1 - 57
1.3.1	Structural Beam Elements (block structure liner create Command)	1 - 57
1.3.1.1	Structural (Beam) Element Formulation	1 - 57
1.3.1.2	Structural Element Generation	1 - 62
1.3.1.3	Structural Element Properties	1 - 64
1.3.1.4	End Conditions and Applied Pressure	1 - 67
1.3.1.5	Summary of Commands Associated with Structural Elements	1 - 68
1.3.1.6	Example Application – Inelastic Material Behavior of a Cantilever Beam	1 - 75
1.3.1.7	Example Application – Support of a Wedge in a Tunnel Roof ..	1 - 86
1.3.1.8	Example Application – Circular Tunnel Excavation with Interior Support	1 - 93
1.3.1.9	Example Application – Shotcrete Lined Tunnel	1 - 99
1.3.1.10	Example Application – Slope Stabilization	1 - 105
1.3.2	Support Members (block struct support Command)	1 - 109
1.3.2.1	Standard Formulation	1 - 109
1.3.2.2	Load-Rate Dependency	1 - 111
1.3.2.3	Numerical Stability	1 - 113
1.3.2.4	Support Member Properties	1 - 113
1.3.2.5	Summary of Commands Associated with Support Members ..	1 - 114
1.3.2.6	Example Application – Support of Faulted Ground	1 - 116
1.3.2.7	Example Application – Load-Rate Dependent Support	1 - 119
1.4	Material Properties	1 - 124
1.5	Modeling Considerations	1 - 125
1.5.1	2D/3D Equivalence	1 - 125
1.5.2	Symmetry Conditions	1 - 130
1.5.3	Equilibrium Conditions	1 - 130
1.5.4	Sign Convention	1 - 131
1.6	Selecting Input parameters For Different Types of Rockbolts	1 - 132
1.6.1	Introduction	1 - 132
1.6.2	Grout Shear Strength	1 - 134
1.6.3	Rockbolt Segment Length	1 - 134
1.6.4	Coupling Shear Stiffness	1 - 135
1.6.5	Rupture Strain	1 - 135
1.6.6	Modeling a Fully Grouted Rockbolt	1 - 135
1.6.7	Modeling a Mechanically Anchored Rockbolt	1 - 139
1.6.8	Modeling a Split Set Rockbolt	1 - 142
1.6.9	Modeling a Swellex Rockbolt	1 - 146
1.6.10	Modeling Rockbolt Pretensioning	1 - 149
1.7	References	1 - 152

2 FLUID FLOW IN JOINTS

2.1	Introduction	2 - 1
2.2	Fluid-Flow Formulations	2 - 3
2.2.1	Basic Algorithm – Transient Flow of a Compressible Fluid	2 - 3
2.2.2	Steady-State Flow Algorithm	2 - 7
2.2.3	Transient Flow of an Incompressible Fluid	2 - 7
2.2.4	Transient Flow of a Compressible Gas	2 - 10
2.2.5	Two-Phase Flow in Joints	2 - 11
2.2.6	Modifying Joint Flow Rate and Simulating Viscoplastic Flow in Joints	2 - 17
2.2.7	Fluid Boundary Logic	2 - 20
2.2.8	One-Way Thermal-Hydraulic Coupling	2 - 22
2.3	Hydraulic Behavior of Rock Joints	2 - 23
2.3.1	Parallel Plate Model	2 - 23
2.3.2	Fluid Flow Properties and Units	2 - 24
2.4	Calculation Modes and Commands for Fluid-Flow Analysis	2 - 25
2.4.1	Selection of Calculation Mode	2 - 26
2.4.2	Properties	2 - 29
2.4.3	Boundary Conditions	2 - 30
2.4.4	Initialization of Fluid Pressures in Domains	2 - 31
2.4.5	Initialization of Pore Pressures in Blocks	2 - 32
2.4.6	Solution	2 - 35
2.4.7	Output Options	2 - 36
2.5	Verification and Example Problems	2 - 37
2.5.1	Heave of a Rock Layer	2 - 37
2.5.2	Example Application of the Fluid Boundary	2 - 40
2.5.3	Steady-State Fluid Flow with Free Surface	2 - 44
2.5.4	Pressure Distribution in a Fracture with Uniform Permeability (Aperture)	2 - 49
2.5.5	Transient Fluid Flow in a Single Joint in an Elastic Medium	2 - 55
2.5.6	Transient One-Dimensional Gas Flow	2 - 64
2.5.7	Filling of a Horizontal Joint – No Capillary Effects	2 - 70
2.5.8	Filling of a Horizontal Joint by the Capillary Forces Only	2 - 77
2.5.9	Containment of Gas Inside a Cavity – Single Horizontal Joint	2 - 82
2.5.10	Containment of Gas Inside a Cavern – Jointed Rock Mass	2 - 88
2.5.11	Thermal-Mechanical-Fluid Flow Example	2 - 92
2.6	References	2 - 99

3 THERMAL ANALYSIS

3.1	Introduction	3 - 1
3.2	Formulation	3 - 2
3.2.1	Basic Equations	3 - 2
3.2.2	Diffusion Equation – Explicit Algorithm	3 - 3
3.2.3	Stability and Accuracy of the Explicit Scheme	3 - 4
3.2.4	Diffusion Equation – Implicit Thermal Logic	3 - 5
3.2.5	Stability and Accuracy of the Implicit Scheme	3 - 7
3.2.6	Thermal-Stress Coupling	3 - 8
3.3	Solving Thermal-Only and Coupled-Thermal Problems	3 - 9
3.3.1	Thermal Analysis	3 - 9
3.3.2	Thermal-Mechanical Analysis	3 - 10
3.3.3	Heat Transfer across Joints	3 - 12
3.3.4	Thermal Boundary Locations	3 - 14
3.4	Input Instructions for Thermal Analysis	3 - 15
3.4.1	UDEEC Commands	3 - 15
3.4.2	FISH Variables	3 - 22
3.5	Systems of Units for Thermal Analysis	3 - 23
3.6	Verification Examples	3 - 25
3.6.1	Conduction through a Composite Wall	3 - 25
3.6.2	Thermal Response of a Heat-Generating Slab	3 - 32
3.6.3	Heating of a Hollow Cylinder	3 - 39
3.6.4	Infinite Line Heat Source in an Infinite Medium	3 - 48
3.7	References	3 - 61

4 DYNAMIC ANALYSIS

4.1	Overview	4 - 1
4.2	Dynamic Formulation	4 - 2
4.3	Dynamic Modeling Considerations	4 - 3
4.3.1	Dynamic Loading and Boundary Conditions	4 - 3
4.3.1.1	Application of Dynamic Input	4 - 4
4.3.1.2	Baseline Correction	4 - 7
4.3.1.3	Quiet Boundaries	4 - 8
4.3.1.4	Free-Field Boundaries	4 - 10
4.3.1.5	Deconvolution and Selection of Dynamic Boundary Conditions	4 - 14
4.3.1.6	Hydrodynamic Pressures	4 - 21
4.3.2	Wave Transmission	4 - 28
4.3.2.1	Accurate Wave Propagation	4 - 28
4.3.2.2	Filtering	4 - 34

4.3.3	Mechanical Damping	4 - 37
4.3.3.1	Rayleigh Damping	4 - 38
4.3.3.2	Example Application of Rayleigh Damping	4 - 40
4.3.3.3	Guidelines for Selecting Rayleigh Damping Parameters	4 - 44
4.3.3.4	Local Damping for Dynamic Simulations	4 - 47
4.4	Solving Dynamic Problems	4 - 49
4.4.1	General Methodology	4 - 49
4.4.2	Illustration of Procedures: Stability of a Jointed-Rock Slope	4 - 50
4.5	Validation Examples	4 - 56
4.5.1	Natural Periods of an Elastic Column	4 - 56
4.5.2	Slip Induced by Harmonic Shear Wave	4 - 60
4.5.3	Line Source in an Infinite Elastic Medium with a Single Discontinuity	4 - 72
4.6	Dynamic Wizard	4 - 92
4.6.1	Signal Preprocessing for Seismic Analysis	4 - 92
4.7	References	4 - 99

TABLES

Table 1.1	Keywords associated with block struct reinforce command	1 - 14
Table 1.2	Keywords associated with block structure cable command	1 - 28
Table 1.3	Keywords associated with block struct rockbolt command	1 - 40
Table 1.4	Keywords associated with block struct liner command	1 - 69
Table 1.5	Keywords associated with block struct beam command	1 - 72
Table 1.6	Joint set orientations	1 - 99
Table 1.7	Support properties for profile props, sticks and yielding props (CSIR 1993) ..	1 - 114
Table 1.8	Keywords associated with block struct support command	1 - 115
Table 1.9	Systems of units – structural elements	1 - 124
Table 1.10	Parameters for fully grouted rockbolt	1 - 136
Table 1.11	Parameters for mechanically anchored rockbolt	1 - 139
Table 1.12	Parameters for split set rockbolt	1 - 143
Table 1.13	Parameters for swellex rockbolt	1 - 146
Table 2.1	Typical SI units for fluid flow parameters	2 - 24
Table 2.2	Summary of fluid flow commands	2 - 25
Table 2.3	Poroelastic constants for some rocks (Detournay and Cheng 1993)	2 - 34
Table 3.1	Summary of block thermal keywords	3 - 15
Table 3.2	System of SI units for thermal problems	3 - 23
Table 3.3	System of Imperial units for thermal problems	3 - 23
Table 3.4	Problem specifications	3 - 25
Table 3.5	Comparison of UDEC results and the analytical solution	3 - 31
Table 4.1	Moduli appropriate to various deformation modes	4 - 56
Table 4.2	Material properties	4 - 57
Table 4.3	Comparison of theoretical and calculated (UDEC) dynamic period T of oscillation for three modes	4 - 57

FIGURES

Figure 1.1	Axial behavior of local reinforcement systems	1 - 4
Figure 1.2	Shear behavior of reinforcement system	1 - 6
Figure 1.3	Assumed reinforcement geometry after shear displacement, Δu_s	1 - 7
Figure 1.4	Orientation of shear and axial springs representing reinforcement prior to and after shear displacement	1 - 8
Figure 1.5	Resolution of reinforcement shear and axial forces into components parallel and perpendicular to discontinuity	1 - 11
Figure 1.6	Slope with steeply dipping foliation planes	1 - 16
Figure 1.7	Slope failure by reverse toppling	1 - 17
Figure 1.8	Stabilization of slope by reinforcement	1 - 17
Figure 1.9	Conceptual mechanical representation of fully bonded reinforcement which accounts for shear behavior of the grout annulus	1 - 18
Figure 1.10	Cable material behavior for cable elements	1 - 19
Figure 1.11	Grout material behavior for cable elements	1 - 20
Figure 1.12	Geometry of triangular finite difference zone and transgressing reinforcement used in distinct element formulation	1 - 22
Figure 1.13	Axial force and displacement vectors for pull-test	1 - 32
Figure 1.14	Cable grout shear force versus displacement at node in small block	1 - 33
Figure 1.15	Material behavior of shear coupling spring for rockbolt elements	1 - 35
Figure 1.16	Material behavior of normal coupling spring for rockbolt elements	1 - 37
Figure 1.17	Rockbolt element in grid; velocity applied at top end node	1 - 42
Figure 1.18	Rockbolt pull force (N) versus rockbolt axial displacement (meters) for a single 25 mm grouted rockbolt	1 - 46
Figure 1.19	Rockbolt pull force (N) versus rockbolt axial displacement (meters) for a single 25 mm grouted rockbolt – with displacement weakening	1 - 47
Figure 1.20	Rockbolt pull force (N) versus rockbolt axial displacement (meters) for a single 25 mm grouted rockbolt – with 5 MPa in-plane confinement and zero out-of-plane confinement	1 - 48
Figure 1.21	Rockbolt pull force (N) versus rockbolt axial displacement (meters) for a single 25 mm grouted rockbolt – with 5 MPa in-plane confinement plus a reduction factor and zero out-of-plane confinement	1 - 49
Figure 1.22	Rockbolt pull force (N) versus rockbolt axial displacement (meters) for a single 25 mm grouted rockbolt – with tensile rupture	1 - 50
Figure 1.23	Rockbolt shear force (N) versus rockbolt shear displacement (meters) for a single 25 mm grouted rockbolt	1 - 55
Figure 1.24	Deformed shape of 25 mm diameter rockbolt at end of shear test	1 - 55
Figure 1.25	Rockbolt shear force (N) versus rockbolt shear displacement (meters) for a single 25 mm grouted rockbolt – with tensile rupture	1 - 56
Figure 1.26	Deformed shape of 25 mm diameter rockbolt following rupture at end of shear test	1 - 56

Figure 1.27	Local stiffness matrix for structural element representation of excavation support	1 - 58
Figure 1.28	Lumped mass representation of structure used in explicit formulation	1 - 59
Figure 1.29	Demonstration of interface slip and large displacement capabilities of explicit structural element formulation	1 - 59
Figure 1.30	Typical moment-thrust diagram	1 - 60
Figure 1.31	Parameters to define structural element locations	1 - 63
Figure 1.32	Shape factors and inertial moments for different shapes	1 - 66
Figure 1.33	Moment-thrust diagram – at initial compressive and tensile strengths	1 - 82
Figure 1.34	Moment-thrust diagram – include residual compressive and tensile strengths	1 - 83
Figure 1.35	Moment-thrust diagram – with zero tensile strength and crack depth ratio = 0.33	1 - 84
Figure 1.36	Moment-thrust diagram – input P-M diagram table	1 - 85
Figure 1.37	Lined tunnel with wedge in roof	1 - 86
Figure 1.38	Case 1: elastic solution	1 - 90
Figure 1.39	Case 2: yield strength = residual strength = 18 MPa	1 - 91
Figure 1.40	Case 3: yield strength = 18 MPa, residual strength = 16.7 MPa	1 - 91
Figure 1.41	Case 4: two layers of lining	1 - 92
Figure 1.42	Case 4: elastic solution for two layers of lining	1 - 92
Figure 1.43	Conceptual representation of support reaction and ground reaction curves ..	1 - 94
Figure 1.44	Zoning for <i>UDEC</i> model of circular tunnel excavation	1 - 96
Figure 1.45	Comparison of ground reaction/support reaction lines	1 - 98
Figure 1.46	Shotcrete applied in 300° arc on tunnel periphery	1 - 100
Figure 1.47	Axial force distribution in shotcrete lining – residual yield strength = 20 MPa	1 - 103
Figure 1.48	Tensile failure locations in shotcrete – residual yield strength = 20 MPa	1 - 103
Figure 1.49	Moment-thrust diagram for tensile yield strength = 20 MPa and compressive yield strength = 40 MPa	1 - 104
Figure 1.50	Axial force distribution in shotcrete lining – residual yield strength = 10 MPa	1 - 104
Figure 1.51	Slope cut in a jointed rock	1 - 105
Figure 1.52	Unsupported slope is unstable	1 - 106
Figure 1.53	Slope is stabilized with shotcrete lining	1 - 107
Figure 1.54	Force-displacement behavior for standard support model	1 - 109
Figure 1.55	Force-displacement behavior including load-rate dependent support force ..	1 - 112
Figure 1.56	Support members before loading	1 - 116
Figure 1.57	Force-displacement relation for support in example problem	1 - 116
Figure 1.58	Support members after loading	1 - 118
Figure 1.59	Model test for rate-dependent support members	1 - 119
Figure 1.60	Axial force versus displacement response for left prop	1 - 122

Figure 1.61	Axial force versus displacement response for right prop unloading	1 - 123
Figure 1.62	Axial force versus displacement response in left prop for right prop unloading	1 - 123
Figure 1.63	Actual axial forces in vertically loaded rockbolt at 2 m spacing (spacing given)	1 - 129
Figure 1.64	Scaled axial forces in vertically loaded rockbolt at 2 m spacing (spacing not given)	1 - 130
Figure 1.65	Results of pull tests by Stillborg (1994)	1 - 133
Figure 1.66	UDEC simulation of pullout test of 20 mm resin grouted rockbolt.	1 - 136
Figure 1.67	UDEC simulation of pull test of a 17 mm mechanically anchored rockbolt. .	1 - 140
Figure 1.68	UDEC simulation of pull test of a 39 mm split set rockbolt.	1 - 143
Figure 1.69	UDEC simulation of pull test of a 26 mm swellex rockbolt.	1 - 147
Figure 1.70	Rock displacements and rockbolt forces resulting from pretensioning a rock- bolt.	1 - 150
Figure 2.1	Fluid/solid interaction in discontinua	2 - 1
Figure 2.2	Flow in joints modeled as flow between domains	2 - 3
Figure 2.3	Relation between hydraulic aperture, a , and joint normal stress, σ_n , in UDEC	2 - 5
Figure 2.4	Extreme example in which the speed of propagation depends on system stiff- ness	2 - 9
Figure 2.5	Capillary pressure curve as a function of saturation and parameter β	2 - 14
Figure 2.6	Flow-gradient relation for Newtonian fluid in UDEC	2 - 18
Figure 2.7	Flow-gradient relation for Bingham fluid in UDEC	2 - 18
Figure 2.8	Porous medium mesh	2 - 20
Figure 2.9	Elements in porous medium mesh	2 - 22
Figure 2.10	Decomposition of stresses acting on a porous, elastic rock	2 - 33
Figure 2.11	Heave of a rock layer	2 - 38
Figure 2.12	UDEC model for fluid boundary example	2 - 40
Figure 2.13	Fluid pressure field	2 - 42
Figure 2.14	Figure showing definition of terms in Dupuit's formula	2 - 44
Figure 2.15	UDEC problem geometry for verification of fluid flow logic	2 - 45
Figure 2.16	UDEC steady-state flow rates	2 - 47
Figure 2.17	UDEC domain pressures	2 - 47
Figure 2.18	Model geometry and boundary conditions	2 - 49
Figure 2.19	Comparison of analytical and UDEC solutions for joint fluid pressure (P / P_0) at various distances (x/l) in a fracture with zero initial pressure at $x = 0$.	2 - 51
Figure 2.20	UDEC model for incompressible flow in a single joint	2 - 56
Figure 2.21	Fluid pressure histories at A, B and C for a 1-second fluid timestep	2 - 57
Figure 2.22	Fluid pressure histories at A, B and C for a 10-second fluid timestep	2 - 57
Figure 2.23	Fluid pressure histories at A, B and C for a 10-second fluid timestep; run to steady-state flow	2 - 58
Figure 2.24	Fluid pressure histories at A, B and C for compressible flow	2 - 58

Figure 2.25	Fluid pressure histories at A, B and C for compressible flow; run to steady-state	2 - 59
Figure 2.26	UDEC model for 1D gas flow	2 - 66
Figure 2.27	Gas pressure along joint (Ψ versus ξ) at time = 0.5	2 - 69
Figure 2.28	Gas pressure along joint (Ψ versus ξ) at time = 2.0	2 - 69
Figure 2.29	Geometry of the UDEC model	2 - 70
Figure 2.30	Wetting fluid pressure in the joint after 1.43 s	2 - 71
Figure 2.31	Saturation of the joint after 1.43 s	2 - 72
Figure 2.32	Wetting fluid pressure histories at the points along the joint	2 - 72
Figure 2.33	Saturation histories at the points along the joint	2 - 73
Figure 2.34	Location of fluid front (distance from the left boundary in meters) as a function of time (seconds). Comparison of the UDEC solution (crosses) with analytical solution (line).	2 - 73
Figure 2.35	Wetting fluid pressures along the joint after .014 s	2 - 77
Figure 2.36	Saturation along the joint after .014 s	2 - 78
Figure 2.37	Wetting fluid pressure histories at the points along the joint	2 - 78
Figure 2.38	Saturation histories at the points along the joint	2 - 79
Figure 2.39	Geometry of the model	2 - 82
Figure 2.40	Wetting fluid pressure along the joint after .00013 s	2 - 83
Figure 2.41	Saturation along the joint after .00013 s	2 - 83
Figure 2.42	Model displacements after .00013 s	2 - 84
Figure 2.43	Non-wetting fluid pressure histories at the points along the joint	2 - 84
Figure 2.44	Saturation at the points along the joint	2 - 85
Figure 2.45	Geometry of the model	2 - 88
Figure 2.46	Non-wetting fluid pressures after 0.25 s	2 - 89
Figure 2.47	Saturation of the joints in the model after 0.25 s	2 - 89
Figure 2.48	UDEC model for thermal-mechanical-fluid flow example	2 - 93
Figure 2.49	Fluid pressure versus thermal time histories for transient flow analysis	2 - 94
Figure 2.50	Fluid pressure versus thermal time histories for steady-state flow analysis ..	2 - 94
Figure 3.1	Heat flow into gridpoint k	3 - 4
Figure 3.2	General solution procedure for thermal-mechanical analysis	3 - 11
Figure 3.3	Subdivision of zones at contacts	3 - 13
Figure 3.4	Typical zoning of rigid block	3 - 13
Figure 3.5	Zones that may cause inaccuracy	3 - 14
Figure 3.6	Composite wall	3 - 25
Figure 3.7	Idealization of the wall for the UDEC model	3 - 29
Figure 3.8	Zone distribution	3 - 29
Figure 3.9	Steady-state temperature distribution	3 - 30
Figure 3.10	Temperature vs distance comparison between UDEC and analytical solution	3 - 31
Figure 3.11	Heat-generating slab showing initial and boundary conditions	3 - 32
Figure 3.12	Model conditions for heat-generating slab	3 - 34

Figure 3.13	<i>UDEC</i> zone distribution	3 - 34
Figure 3.14	Temperature evolution in the center of the slab	3 - 37
Figure 3.15	Temperature distribution at steady-state	3 - 38
Figure 3.16	<i>UDEC</i> and analytical temperature distributions at thermal time = 0.1, 0.5 and 5.0 seconds (analytical values = odd-numbered tables; numerical values = even-numbered tables)	3 - 38
Figure 3.17	<i>UDEC</i> grid for heating of a hollow cylinder	3 - 40
Figure 3.18	Temperature distribution at steady state for heating of a hollow cylinder ...	3 - 46
Figure 3.19	Radial stress distribution at steady state for heating of a hollow cylinder ...	3 - 46
Figure 3.20	Tangential stress distribution at steady state for heating of a hollow cylinder	3 - 47
Figure 3.21	Axial stress distribution at steady state for heating of a hollow cylinder	3 - 47
Figure 3.22	<i>UDEC</i> grid for an infinite line heat source	3 - 49
Figure 3.23	Close-up view of zoning in blocks	3 - 50
Figure 3.24	Temperature distribution at 1 year	3 - 59
Figure 3.25	Radial displacement distribution at 1 year	3 - 59
Figure 3.26	Radial and tangential stress distributions at 1 year	3 - 60
Figure 4.1	Types of dynamic loading and boundary conditions in <i>UDEC</i>	4 - 3
Figure 4.2	Primary and reflected waves in a bar: stress input through a quiet boundary	4 - 7
Figure 4.3	The baseline correction process	4 - 8
Figure 4.4	Model for seismic analysis of surface structures and free-field mesh	4 - 11
Figure 4.5	x -velocity histories at top of model with free-field boundaries	4 - 13
Figure 4.6	Seismic input to <i>UDEC</i>	4 - 14
Figure 4.7	Layered system analyzed by <i>SHAKE</i> (layer properties are shear modulus, G , density, ρ , and damping fraction, ζ)	4 - 15
Figure 4.8	Deconvolution procedure for a rigid base (after Mejia and Dawson 2006)	4 - 17
Figure 4.9	Deconvolution procedure for a compliant base (after Mejia and Dawson 2006)	4 - 17
Figure 4.10	Compliant-base deconvolution procedure for a typical case (after Mejia and Dawson 2006)	4 - 19
Figure 4.11	Compliant-base deconvolution procedure for another typical case (after Mejia and Dawson 2006)	4 - 19
Figure 4.12	Embankment analyzed with a rigid and compliant base (after Mejia and Dawson 2006)	4 - 20
Figure 4.13	Computed accelerations at crest of embankment (after Mejia and Dawson 2006)	4 - 20
Figure 4.14	Hydrodynamic pressure acting on a rigid dam with a vertical upstream face	4 - 21
Figure 4.15	Dam model with hydrodynamic pressure boundary on upstream face	4 - 24
Figure 4.16	Comparison of x -displacement at top of dam	4 - 25
Figure 4.17	Column of variable-sized blocks subjected to triangular-shaped impulse load at base	4 - 30

Figure 4.18	Input wave (solid) at base and calculated wave (dashed) at top of column of rigid block model	4 - 30
Figure 4.19	Column of variable-sized blocks subdivided into finite difference zones	4 - 31
Figure 4.20	Input wave (solid) at base and calculated wave (dashed) at top of column of deformable block model	4 - 31
Figure 4.21	Unfiltered velocity history	4 - 35
Figure 4.22	Unfiltered power spectral density plot	4 - 35
Figure 4.23	Filtered velocity history at 15 Hz	4 - 36
Figure 4.24	Results of filtering at 15 Hz	4 - 36
Figure 4.25	Variation of normalized critical damping ratio with angular frequency	4 - 39
Figure 4.26	Plot of vertical displacement versus time, for a single block contacting on a rigid base with gravity suddenly applied (no damping)	4 - 42
Figure 4.27	Plot of vertical displacement versus time, for a single block contacting on a rigid base with gravity suddenly applied (mass and stiffness damping) ..	4 - 43
Figure 4.28	Plot of vertical displacement versus time, for a single block contacting on a rigid base with gravity suddenly applied (mass damping only)	4 - 43
Figure 4.29	Plot of vertical displacement versus time, for a single block contacting on a rigid base with gravity suddenly applied (stiffness damping only)	4 - 44
Figure 4.30	Plot of velocity spectrum versus frequency	4 - 45
Figure 4.31	Comparison of fundamental wavelengths for bars with varying end conditions	4 - 46
Figure 4.32	Displacement history – 5% Rayleigh damping	4 - 48
Figure 4.33	Displacement history – 5% local damping	4 - 49
Figure 4.34	Initial equilibrium of slope cut in jointed rock	4 - 51
Figure 4.35	Input velocity (history 2) and calculated velocity (history 3) at top of model without slope	4 - 53
Figure 4.36	Slope failure resulting from dynamic loading	4 - 55
Figure 4.37	x -velocity histories at base, slope face and remote from slope	4 - 55
Figure 4.38	Transmission and reflection of incident harmonic wave at a discontinuity ..	4 - 60
Figure 4.39	Problem geometry and boundary conditions for the problem of slip induced by harmonic shear wave	4 - 64
Figure 4.40	Time variation of shear stress at points A and B for elastic discontinuity (cohesion = 2.5 MPa)	4 - 65
Figure 4.41	Time variation of shear stress at points A and B for slipping discontinuity (cohesion = 0.5 MPa)	4 - 65
Figure 4.42	Time variation of shear stress at points A and B for slipping discontinuity (cohesion = 0.1 MPa)	4 - 66
Figure 4.43	Time variation of shear stress at points A and B for slipping discontinuity (cohesion = 0.02 MPa)	4 - 66
Figure 4.44	Comparison of transmission, reflection and absorption coefficients; points denote UDEEC results	4 - 67
Figure 4.45	Problem geometry for an explosive source near a slip-prone discontinuity ..	4 - 72
Figure 4.46	Dimensionless analytical results for slip history at point <i>P</i> (Day 1985) (dimensionless slip = $(4h \rho \beta^2 / m_o) \delta u$; dimensionless time = $t\beta/h$)	4 - 74

Figure 4.47	Problem geometry and boundary conditions for the <i>UDEC</i> analysis	4 - 74
Figure 4.48	<i>UDEC</i> model showing semicircular source and joints	4 - 75
Figure 4.49	Input radial velocity time history prescribed at $r = 0.05 h$ (dimensionless velocity = $(h^2 \rho \beta / m_o) v$; dimensionless time = $t \beta / h$)	4 - 77
Figure 4.50	Comparison of analytical results (history 4) and numerical results (history 8) for dynamic slip at point <i>P</i> , using the Coulomb joint model	4 - 78
Figure 4.51	Comparison of analytical results (history 4) and numerical results (history 8) for dynamic slip at point <i>P</i> , using the continuously yielding model	4 - 79
Figure 4.52	Horizontal acceleration time history at elevation of 400 ft (upward-propagating motion from deconvolution analysis)	4 - 92
Figure 4.53	Import input into the wizard	4 - 93
Figure 4.54	Original input records, amplitude spectrum and filter	4 - 94
Figure 4.55	Filtered input records, amplitude spectrum	4 - 95
Figure 4.56	Waveform before baseline correction	4 - 96
Figure 4.57	Waveform after baseline correction	4 - 96
Figure 4.58	Save processed velocity in a table	4 - 97
Figure 4.59	Processed velocity record	4 - 98

EXAMPLES

Example 1.1	Reinforced slope	1 - 15
Example 1.2	Simulation of a pull-test for a grouted cable anchor	1 - 29
Example 1.3	Rockbolt pullout tests	1 - 43
Example 1.4	Rockbolt shear tests	1 - 51
Example 1.5	Inelastic material behavior of a cantilever beam	1 - 76
Example 1.6	Lined tunnel with wedge in roof	1 - 87
Example 1.7	Circular excavation with interior support	1 - 96
Example 1.8	Shotcrete lined tunnel	1 - 101
Example 1.9	Slope stabilization	1 - 107
Example 1.10	Support of faulted ground	1 - 117
Example 1.11	Load-rate dependent support	1 - 119
Example 1.12	Axial loading of rockbolts at 2 m spacing	1 - 128
Example 1.13	Simulation of a pull-test for a fully grouted rockbolt	1 - 136
Example 1.14	Simulation of a pull-test for a mechanically anchored rockbolt	1 - 140
Example 1.15	Simulation of a pull-test for a split set rockbolt	1 - 143
Example 1.16	Simulation of a pull-test for a swellex rockbolt	1 - 147
Example 1.17	Simulation of a pull-test for a swellex rockbolt	1 - 150
Example 2.1	Heave of a rock layer	2 - 39
Example 2.2	Application of the fluid boundary logic	2 - 42
Example 2.3	Steady-state fluid flow with a free surface	2 - 48
Example 2.4	Pressure distribution in a fracture with uniform permeability	2 - 51
Example 2.5	Incompressible transient flow in a single joint in an elastic medium	2 - 59
Example 2.6	Compressible transient flow in a single joint in an elastic medium	2 - 62
Example 2.7	Analytical solution and empirical fit for 1D gas flow	2 - 64
Example 2.8	Analytical solution for pressure at $x = 10$	2 - 66
Example 2.9	Transient one-dimensional gas flow	2 - 67
Example 2.10	Injection of water in gas-filled joint	2 - 74
Example 2.11	Filling of the joint with water due to capillary forces only	2 - 80
Example 2.12	Containment of gas inside a cavity – single joint	2 - 86
Example 2.13	Containment of gas inside a cavity – jointed rock mass	2 - 90
Example 2.14	Thermal-mechanical-fluid flow with incompressible transient flow	2 - 95
Example 2.15	Thermal-mechanical-fluid flow assuming steady-state flow	2 - 97
Example 3.1	Conduction through a composite wall	3 - 27
Example 3.2	Thermal response of a heat-generating slab	3 - 35
Example 3.3	Heating of a hollow cylinder	3 - 41
Example 3.4	Infinite line heat source in an infinite medium	3 - 51
Example 3.5	Exponential integral function	3 - 58
Example 4.1	Shear wave propagation in a vertical column	4 - 6

Example 4.2	Shear wave loading of a model with free-field boundaries	4 - 12
Example 4.3	Hydrodynamic pressure acting on a dam	4 - 26
Example 4.4	Column of variable-sized blocks subjected to impulse load at base	4 - 32
Example 4.5	Block under gravity – undamped and 3 critically damped cases	4 - 40
Example 4.6	Continuation of Example 4.5 with 5% Rayleigh damping	4 - 47
Example 4.7	Continuation of Example 4.5 with 5% local damping	4 - 47
Example 4.8	Initial conditions for the slope problem	4 - 50
Example 4.9	Dynamic excitation of the slope problem	4 - 53
Example 4.10	Data file for confined compression	4 - 58
Example 4.11	Data file for unconfined compression	4 - 58
Example 4.12	Data file for shear	4 - 59
Example 4.13	Listing of “avper.fis”: function to compute average period	4 - 59
Example 4.14	Verification of dynamic slip – four complete simulations	4 - 67
Example 4.15	Line source in an infinite elastic medium with a discontinuity	4 - 79
Example 4.16	Listing of “VEL_INP.FIS”: function to calculate velocity input	4 - 84
Example 4.17	Listing of “ANA_SLP.FIS”: function to calculate Day solution for dynamic slip	4 - 87

