

## TABLE OF CONTENTS

---

### 1 Seismic-Induced Groundfall

1.1	Problem Statement .....	1 - 1
1.2	<i>UDEC</i> Analysis .....	1 - 2
1.3	Listing of Data File .....	1 - 9

### 2 Open Stopping Using Vertical Retreat

2.1	Problem Statement .....	2 - 1
2.2	<i>UDEC</i> Analysis .....	2 - 3
2.3	Listing of Data File .....	2 - 5

### 3 Tunnel Support Loading

3.1	Problem Statement .....	3 - 1
3.2	<i>UDEC</i> Analysis .....	3 - 2
3.3	Listing of Data File .....	3 - 7

### 4 Gravity Dam: Fluid Flow and Dynamic Loading

4.1	Problem Statement .....	4 - 1
4.2	<i>UDEC</i> Analysis .....	4 - 1
4.3	Listing of Data File .....	4 - 11

### 5 Cement Grouting Simulation

5.1	Problem Statement .....	5 - 1
5.2	<i>UDEC</i> Analysis .....	5 - 2
5.3	References .....	5 - 3
5.4	Listing of Data File .....	5 - 8

### 6 Thermomechanical Analysis of a Waste Emplacement Drift

6.1	Problem Statement .....	6 - 1
6.2	<i>UDEC</i> Analysis .....	6 - 3
6.3	Results .....	6 - 5
6.4	References .....	6 - 8
6.5	Listing of Data File .....	6 - 8

**7 Inflow into a Tunnel**

7.1	Problem Statement .....	7 - 1
7.2	<i>UDEC</i> Analysis .....	7 - 2
7.3	Listing of Data File .....	7 - 9

**8 Flow through a Jointed Rock Slope**

8.1	Problem Statement .....	8 - 1
8.2	<i>UDEC</i> Analysis .....	8 - 2
8.3	Listing of Data File .....	8 - 6

**9 Flow from a Borehole in a Biaxial Stress Field**

9.1	Problem Statement .....	9 - 1
9.2	<i>UDEC</i> Analysis .....	9 - 2
9.3	Listing of Data File .....	9 - 5

**10 Influence of the Placement of Backfill in a Deep Longwall Excavation**

10.1	Problem Statement .....	10 - 1
10.2	<i>UDEC</i> Analysis .....	10 - 4
10.3	Listing of Data File .....	10 - 9

**11 Shotcrete and Cable Support**

11.1	Problem Statement .....	11 - 1
11.2	<i>UDEC</i> Analysis .....	11 - 3
11.3	Listing of Data Files .....	11 - 6

**12 Blocks Bouncing down Slope**

12.1	Problem Statement .....	12 - 1
12.2	<i>UDEC</i> Analysis .....	12 - 2
12.3	Listing of Data File .....	12 - 4

**13 Step-Path Failure of Rock Slopes**

13.1	Problem Statement .....	13 - 1
13.2	<i>UDEC</i> Analysis .....	13 - 2
13.3	Listing of Data File .....	13 - 7

**14 Hydraulic Fracturing Simulation**

14.1	Problem Statement .....	14 - 1
14.1.1	Data for the Simulations .....	14 - 1
14.2	<i>UDEC</i> Analyses .....	14 - 2
14.2.1	Case 1 .....	14 - 2
14.2.1.1	<i>UDEC</i> Model .....	14 - 2
14.2.1.2	Analytical Solution .....	14 - 3
14.2.1.3	<i>UDEC</i> Results .....	14 - 3
14.2.2	Case 2 .....	14 - 4
14.2.2.1	<i>UDEC</i> Model .....	14 - 4
14.2.2.2	<i>UDEC</i> Results .....	14 - 6
14.3	Summary .....	14 - 11
14.4	References .....	14 - 11
14.5	Listing of Data Files .....	14 - 12

**TABLES**

---

Table 2.1	Properties of rock types .....	2 - 2
Table 6.1	Thermal and mechanical properties used in thermomechanical analysis of a waste emplacement drift .....	6 - 2
Table 14.1	Data for the simulations .....	14 - 1

**FIGURES**

Figure 1.1	<i>UDEC</i> model for seismic-induced groundfall .....	1 - 1
Figure 1.2	Stress distribution around excavation at end of excavation stage .....	1 - 3
Figure 1.3	Stress distribution in roof of excavation after 0.02 sec. (applied stress = $1.25 \times \cos(2\pi 100t)$ ) .....	1 - 3
Figure 1.4	y-displacement histories for two points on excavation boundary (applied stress = $1.25 \times \cos(2\pi 100t)$ ) .....	1 - 4
Figure 1.5	Plot of y-velocity at top of model (applied stress = $1.25 \times \cos(2\pi 100t)$ ) .....	1 - 5
Figure 1.6	Stress distribution in roof of excavation after 0.02 sec. (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 6
Figure 1.7	y-displacement histories for two points on excavation boundary (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 6
Figure 1.8	Stress distribution around excavation after 0.25 sec. (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 7
Figure 1.9	Stress distribution around excavation after 0.50 sec. (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 7
Figure 1.10	Stress distribution around excavation after 0.75 sec. (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 8
Figure 1.11	Plot of y-velocity at top of model (applied stress = $12.5 \times \cos(2\pi 100t)$ ) .....	1 - 8
Figure 2.1	Initial geometry for blasthole open stoping operation .....	2 - 1
Figure 2.2	Cohesion properties assigned to the <i>UDEC</i> model .....	2 - 3
Figure 2.3	Principal stresses at end of mining sequence .....	2 - 4
Figure 2.4	Changes in <i>xx</i> - and <i>yy</i> -stresses in crown pillar with mining stages History 2: <i>xx</i> -stress, History 3: <i>yy</i> -stress (note: compressive stresses are negative) .	2 - 4
Figure 3.1	Idealized geometry of service tunnel and main tunnel .....	3 - 1
Figure 3.2	<i>UDEC</i> model zoning with service tunnel excavated .....	3 - 3
Figure 3.3	Elastic displacements due to excavation of service tunnel .....	3 - 3
Figure 3.4	Displacements after mining of main tunnel .....	3 - 5
Figure 3.5	Principal stress distribution after mining of main tunnel .....	3 - 5
Figure 3.6	Thrust in liners after water level is raised .....	3 - 6
Figure 3.7	Moment in liners after water level is raised .....	3 - 6
Figure 4.1	<i>UDEC</i> model of gravity dam with principal stresses plotted at Stage 1 .....	4 - 1
Figure 4.2	Principal stress state and displacements at Stage 2 .....	4 - 3
Figure 4.3	<i>x</i> - and <i>y</i> -components of displacement at crest of dam during Stage 2 reservoir filling .....	4 - 3
Figure 4.4	Flow rates at Stage 2 .....	4 - 4
Figure 4.5	Shear and normal displacements along joint at $x = -33.42$ , $y = -30.37$ ....	4 - 4
Figure 4.6	Fluid pressure in domain at location $x = -22.1$ , $y = -26.3$ .....	4 - 5
Figure 4.7	<i>x</i> -velocity histories at dam crest and model base at Stage 3 .....	4 - 7
Figure 4.8	<i>x</i> - and <i>y</i> -displacements at dam crest at Stage 3 .....	4 - 7

Figure 4.9	Joint shear and normal displacement histories at joint beneath dam foundation at Stage 3 .....	4 - 8
Figure 4.10	Displacements, principal stresses and joint shear displacement at Stage 3 ..	4 - 8
Figure 4.11	<i>x</i> -velocity histories at dam crest and model base at Stage 3 .....	4 - 9
Figure 4.12	<i>x</i> - and <i>y</i> -displacements at dam crest at Stage 3 .....	4 - 9
Figure 4.13	Joint shear and normal displacement histories at joint beneath dam foundation at Stage 3 .....	4 - 10
Figure 4.14	Displacements, principal stresses and joint shear displacement at Stage 3 ..	4 - 10
Figure 5.1	<b>UDEC</b> model and initial stress state for grouting simulation .....	5 - 2
Figure 5.2	Flow rates versus hole pressure .....	5 - 4
Figure 5.3	Flow rates for grouting simulation at 10,000 Pa .....	5 - 4
Figure 5.4	Flow rates for grouting simulation at 12,000 Pa .....	5 - 5
Figure 5.5	Flow rates for grouting simulation at 16,000 Pa .....	5 - 5
Figure 5.6	Grout pressures in joints for grouting simulation at 10,000 Pa .....	5 - 6
Figure 5.7	Grout pressures in joints for grouting simulation at 12,000 Pa .....	5 - 6
Figure 5.8	Grout pressures in joints for grouting simulation at 16,000 Pa .....	5 - 7
Figure 6.1	Conceptual model of vertical emplacement concept .....	6 - 1
Figure 6.2	<b>UDEC</b> geometry for thermomechanical analysis of a waste emplacement drift	6 - 4
Figure 6.3	Close-up view of waste emplacement drift .....	6 - 4
Figure 6.4	Principal stress distribution after excavation of the drift .....	6 - 5
Figure 6.5	Displacement vectors after excavation of the drift .....	6 - 6
Figure 6.6	Temperature distribution in the rock at 50 years .....	6 - 6
Figure 6.7	Principal stress distribution in the rock at 50 years .....	6 - 7
Figure 6.8	Shear displacement along the joints at 50 years .....	6 - 7
Figure 7.1	<b>UDEC</b> model for inflow into a tunnel .....	7 - 1
Figure 7.2	Initial total stresses in <b>UDEC</b> model .....	7 - 3
Figure 7.3	Initial pore pressures in <b>UDEC</b> model .....	7 - 3
Figure 7.4	Pore pressures after undrained deformation .....	7 - 4
Figure 7.5	Undrained deformation of the model .....	7 - 5
Figure 7.6	Locations of the history points .....	7 - 6
Figure 7.7	Histories of flow rates during consolidation ( <b>block fluid compressible</b> ) .....	7 - 7
Figure 7.8	Histories of flow rates during the steady-flow calculation ( <b>block fluid steady-state</b> ) .....	7 - 7
Figure 7.9	Histories of flow rates during consolidation ( <b>block fluid incompressible</b> ) ....	7 - 8
Figure 7.10	Pore pressures at steady-state flow .....	7 - 8
Figure 7.11	Flow rates in the joints at steady-state flow .....	7 - 9
Figure 8.1	Problem geometry for example problem involving flow through jointed rock slope .....	8 - 1
Figure 8.2	Problem geometry for example problem involving flow through jointed rock slope .....	8 - 3

Figure 8.3	Water level at right-hand side equal to 6 m (maximum flow rate = $5.6 \times 10^{-5}$ m <sup>3</sup> /sec) .....	8 - 3
Figure 8.4	Water level at right-hand side equal to 8 m (maximum flow rate = $7.4 \times 10^{-5}$ m <sup>3</sup> /sec) .....	8 - 4
Figure 8.5	Water level at right-hand side equal to 9 m (maximum flow rate = $8.1 \times 10^{-5}$ m <sup>3</sup> /sec) .....	8 - 4
Figure 8.6	Water level at right-hand side equal to 10 m (maximum flow rate = $9.4 \times 10^{-5}$ m <sup>3</sup> /sec) .....	8 - 5
Figure 8.7	Slope failure with water level at 10 m .....	8 - 5
Figure 9.1	<b>UDEC</b> model of a borehole in a rock mass containing two orthogonal joint sets .....	9 - 2
Figure 9.2	Flow in joints at 15 seconds after fluid flow initiates from the borehole .....	9 - 3
Figure 9.3	Joint hydraulic apertures at 15 seconds after fluid flow initiates from the borehole .....	9 - 3
Figure 9.4	Fluid pressure histories at points 1, 2, 3, 4 and 5 .....	9 - 4
Figure 10.1	<b>UDEC</b> model of deep longwall excavation .....	10 - 1
Figure 10.2	Cap pressure variation with plastic volumetric strain .....	10 - 3
Figure 10.3	Close-up view of the zoning for the 2.5-m thick seam and the roof .....	10 - 4
Figure 10.4	Second excavation ( <b>block zone cmodel assign null</b> ) step and first fill ( <b>block zone cmodel assign double-yield</b> ) step .....	10 - 5
Figure 10.5	Stress state, 10 m excavated .....	10 - 6
Figure 10.6	Stress state, 20 m excavated and 10 m backfilled .....	10 - 6
Figure 10.7	Stress state, 30 m excavated and 20 m backfilled .....	10 - 7
Figure 10.8	Stress state, 40 m excavated and 30 m backfilled .....	10 - 7
Figure 10.9	Stress state, 50 m excavated and 40 m backfilled .....	10 - 8
Figure 10.10	Stress state, 50 m excavated and 40 m backfilled with Mohr-Coulomb material .....	10 - 8
Figure 11.1	<b>UDEC</b> model of a circular excavation in a rock mass containing a high-angle joint set and a vertical fault – tunnel support with a shotcrete lining and cable bolts .....	11 - 1
Figure 11.2	y-displacement history recorded at a location on the roof wedge – unstable movement .....	11 - 4
Figure 11.3	Close-up view of tunnel showing sliding of roof wedge and failure of shotcrete lining .....	11 - 4
Figure 11.4	y-displacement history recorded at a location on the roof wedge – movement stops .....	11 - 5
Figure 11.5	Close-up view of tunnel showing the stable roof wedge and axial forces in the cables and shotcrete lining .....	11 - 5
Figure 12.1	<b>UDEC</b> model of blocks to be dropped onto the slope .....	12 - 3
Figure 12.2	Position and velocities of the blocks after 25,000 cycles .....	12 - 3
Figure 12.3	Position and velocities of the blocks after 50,000 cycles .....	12 - 4
Figure 13.1	Geometry of simple slope containing en echelon joints .....	13 - 1
Figure 13.2	En echelon joints in slope model .....	13 - 3

Figure 13.3	Continuous joints in slope model .....	13 - 3
Figure 13.4	Step-path failure of slope – factor-of-safety = 1.28 .....	13 - 5
Figure 13.5	Step-path failure depicted by joint maximum shear displacement and rock maximum shear strain .....	13 - 5
Figure 13.6	Continuum failure of slope – factor-of-safety = 1.38 .....	13 - 6
Figure 13.7	Continuous joint shear failure of slope – factor-of-safety = 1.01 .....	13 - 6
Figure 14.1	<b>UDEC</b> model – finite difference zones and fluid pressure in the crack .....	14 - 2
Figure 14.2	Fracture opening along the fracture for Case 1 – line: analytical solution; crosses: <b>UDEC</b> solution .....	14 - 3
Figure 14.3	Displacement vectors at the end of the simulation – Case 1 .....	14 - 4
Figure 14.4	<b>UDEC</b> finite difference zones in a 2 m × 2 m portion of the model .....	14 - 5
Figure 14.5	Fluid pressure at the well (MPa) versus time (sec) .....	14 - 6
Figure 14.6	Width at the well (m) versus time (sec) .....	14 - 7
Figure 14.7	Fluid pressure (MPa) versus distance (m) along the fracture at 10 sec .....	14 - 8
Figure 14.8	Fracture width (m) versus distance (m) along the fracture at 10 sec .....	14 - 9
Figure 14.9	Displacement vectors near the fracture (half fracture shown) at 10 sec. ....	14 - 10



**EXAMPLES**

---

Example 1.1	SEISMIC.DAT .....	1 - 9
Example 2.1	STOPE.DAT .....	2 - 5
Example 3.1	TUNNEL.DAT .....	3 - 7
Example 4.1	DAM.DAT .....	4 - 11
Example 5.1	GROUT.DAT .....	5 - 8
Example 6.1	DRIFT.DAT .....	6 - 8
Example 7.1	INFLOW.DAT .....	7 - 9
Example 8.1	SLOPEFLO.DAT .....	8 - 6
Example 9.1	BH.DAT .....	9 - 5
Example 10.1	LONGWALL.DAT .....	10 - 9
Example 11.1	SUPPORT.DAT .....	11 - 6
Example 11.2	SUP_CAB.FIS .....	11 - 8
Example 12.1	BOUNCE.DAT .....	12 - 4
Example 13.1	STEPPATH.DAT .....	13 - 7
Example 14.1	HF_CASE1.DAT .....	14 - 12
Example 14.2	HF_CASE2.DAT .....	14 - 15

