

TABLE OF CONTENTS

1 INTRODUCTION

1.1	Overview	1 - 1
1.2	Comparison with Other Methods	1 - 3
1.3	General Features	1 - 5
1.4	What's New in <i>UDEC</i> 7.0	1 - 7
1.4.1	New user interface	1 - 7
1.4.2	New Command syntax	1 - 8
1.4.3	Added FISH functionality	1 - 9
1.4.4	Built in Editor (GUI)	1 - 10
1.4.5	Easy Stress Initialization	1 - 10
1.4.6	New Block Creation Tools	1 - 11
1.4.7	Import Geometries (such as DXF)	1 - 12
1.4.8	Rock Support Additional Features	1 - 12
1.4.9	Groups, Extra Variables	1 - 12
1.4.10	3D joint specification	1 - 13
1.4.11	Discrete Fracture Network (DFD)	1 - 13
1.4.12	Factor of Safety Contours	1 - 14
1.4.13	Graphical Information Retrieval	1 - 15
1.4.14	Contact Failure States	1 - 15
1.4.15	Added future Save File Compatibility	1 - 15
1.4.16	GUI project files	1 - 16
1.4.17	Technical Support Dialog	1 - 16
1.4.18	Dynamic Input Wizzard	1 - 16
1.4.19	Updated save/restore system	1 - 16
1.5	Fields of Application	1 - 17
1.6	Guide to the Manual	1 - 19
1.7	Itasca Consulting Group Inc.	1 - 22
1.8	User Support	1 - 23
1.9	References	1 - 24

2 GETTING STARTED

2.1	Installation and Start-up Procedures	2-3
2.1.1	System Requirements	2-3
2.1.2	Installation Procedure	2-3
2.1.3	Components of <i>UDEC</i>	2-4
2.1.4	Memory Allocation	2-4
2.1.5	Utility Software and Graphics Devices	2-5
2.1.6	Start-up	2-7
2.1.7	Version Identification	2-8
2.1.8	Installation Test	2-9
2.2	Running <i>UDEC</i>	2-11
2.2.1	Running <i>UDEC</i> in Menu-Driven Mode	2-11
2.2.1.1	Entering the <i>GIIC</i> and Selecting Analysis Options	2-11
2.2.1.2	Changing <i>GIIC</i> Preferences	2-14
2.2.1.3	Modeling-Stage Tools	2-15
2.2.2	A Simple Tutorial – Use of the <i>GIIC</i>	2-16
2.2.3	Running <i>UDEC</i> in Command-Driven Mode	2-40
2.2.4	A Simple Tutorial – Use of Common Commands	2-41
2.3	Nomenclature	2-46
2.4	The <i>UDEC</i> Model: Subdivision of the Initial Block	2-50
2.5	Command Syntax	2-53
2.6	Mechanics of Using <i>UDEC</i>	2-55
2.6.1	Block Cutting	2-57
2.6.2	Assigning Material Models	2-63
2.6.2.1	Block Models	2-63
2.6.2.2	Joint Models	2-66
2.6.2.3	Example Block and Joint Model Assignment	2-67
2.6.3	Applying Boundary and Initial Conditions	2-69
2.6.4	Stepping to Initial Equilibrium	2-70
2.6.5	Performing Alterations	2-76
2.6.6	Saving/Restoring Problem State	2-77
2.6.7	Summary of Commands for Simple Analyses	2-79
2.7	Sign Conventions	2-81
2.8	Systems of Units	2-83
2.9	Resolution Limits	2-84
2.10	Files	2-85
2.11	References	2-88

3 PROBLEM SOLVING WITH *UDEC*

3.1	General Approach	3-2
3.1.1	Step 1: Define the Objectives for the Model Analysis	3-3
3.1.2	Step 2: Create a Conceptual Picture of the Physical System	3-3
3.1.3	Step 3: Construct and Run Simple Idealized Models	3-4
3.1.4	Step 4: Assemble Problem-Specific Data	3-4
3.1.5	Step 5: Prepare a Series of Detailed Model Runs	3-4
3.1.6	Step 6: Perform the Model Calculations	3-5
3.1.7	Step 7: Present Results for Interpretation	3-5
3.2	Model Generation	3-6
3.2.1	Fitting the <i>UDEC</i> Model to a Problem Region	3-6
3.2.2	Joint Generation	3-9
3.2.2.1	Statistical Joint-Set Generator	3-9
3.2.2.2	Voronoi Tessellation Generator	3-11
3.2.2.3	Examples	3-12
3.2.3	Creating Internal Boundary Shapes	3-19
3.3	Selection of Deformable versus Rigid Blocks	3-25
3.4	Boundary Conditions	3-31
3.4.1	Stress Boundary	3-31
3.4.1.1	Applied Stress Gradient	3-32
3.4.1.2	Changing Boundary Stresses	3-33
3.4.1.3	Printing and Plotting	3-33
3.4.1.4	Caution and Advice	3-34
3.4.2	Displacement Boundary	3-37
3.4.3	Real Boundaries – Choosing the Right Type	3-38
3.4.4	Artificial Boundaries	3-38
3.4.4.1	Symmetry Lines	3-38
3.4.4.2	Boundary Truncation	3-38
3.4.4.3	Boundary-Element Boundary	3-45
3.5	Initial Conditions	3-47
3.5.1	Uniform Stresses in an Unjointed Medium: No Gravity	3-47
3.5.2	Stresses with Gradients in an Unjointed Medium: Uniform Material ..	3-48
3.5.3	Stresses with Gradients in an Unjointed Medium: Nonuniform Material	3-49
3.5.4	Compaction within a Model with Nonuniform Zoning	3-51
3.5.5	Initial Stresses Following a Model Change	3-54
3.5.6	Stresses in a Jointed Medium	3-55
3.6	Loading and Sequential Modeling	3-57

3.7	Choice of Constitutive Model	3 - 69
3.7.1	Deformable-Block Material Models	3 - 69
3.7.2	Joint Material Models	3 - 75
3.7.3	Selection of an Appropriate Model	3 - 77
3.8	Material Properties	3 - 96
3.8.1	Block Properties	3 - 96
3.8.1.1	Mass Density	3 - 97
3.8.1.2	Intrinsic Deformability Properties	3 - 97
3.8.1.3	Intrinsic Strength Properties	3 - 98
3.8.1.4	Post-Failure Properties	3 - 100
3.8.1.5	Extrapolation to Field-Scale Properties	3 - 107
3.8.2	Joint Properties	3 - 111
3.9	Tips and Advice	3 - 113
3.10	Interpretation	3 - 120
3.10.1	Unbalanced Force	3 - 120
3.10.2	Block/Gridpoint Velocities	3 - 120
3.10.3	Plastic Indicators for Block Failure	3 - 121
3.10.4	Histories	3 - 122
3.10.5	Factor of Safety	3 - 122
3.10.5.1	Strength Reduction Method	3 - 122
3.10.5.2	Strength/Stress Ratio	3 - 125
3.11	Modeling Methodology	3 - 127
3.11.1	Modeling of Data-Limited Systems	3 - 127
3.11.2	Modeling of Chaotic Systems	3 - 127
3.11.3	Localization, Physical Instability and Path-Dependence	3 - 129
3.11.4	Multithreading	3 - 130
3.12	References	3 - 131
4	FISH BEGINNER'S GUIDE	
4.1	Introduction and Overview	4 - 1
4.2	Beginner's Guide and Tutorial	4 - 2
5	MISCELLANEOUS	
5.1	UDEC Runtime Benchmark	5 - 1
5.2	Error Reporting	5 - 3
5.2.1	Reporting via the program	5 - 3
5.2.2	Reporting via the Web	5 - 3
5.2.3	Reporting via Email	5 - 3
5.3	Technical Support Service	5 - 3

TABLES

Table 2.1	Maximum number of <i>UDEC</i> blocks in available RAM	2 - 4
Table 2.2	Typographical conventions	2 - 54
Table 2.3	Boundary condition command summary	2 - 69
Table 2.4	Basic commands for simple analyses	2 - 80
Table 2.5	Systems of units – mechanical parameters	2 - 83
Table 3.1	Recommended steps for numerical analysis in geomechanics	3 - 3
Table 3.2	<i>UDEC</i> constitutive models	3 - 72
Table 3.3	<i>UDEC</i> joint constitutive models	3 - 76
Table 3.4	Selected elastic constants (laboratory-scale) for rocks (adapted from Goodman 1980)	3 - 98
Table 3.5	Selected strength properties (laboratory-scale) for rocks (adapted from Goodman 1980)	3 - 99
Table 3.6	Typical values for Hoek-Brown rock-mass strength parameters (adapted from Hoek and Brown 1988)	3 - 110
Table 4.1	Commands that directly refer to <i>FISH</i> names	4 - 4
Table 5.1	<i>UDEC</i> 6.0 runtime calculation rates	5 - 2

FIGURES

Figure 2.1	Print plot dialog	2-5
Figure 2.2	Print setup dialog	2-6
Figure 2.3	UDEC start-up window	2-7
Figure 2.4	UDEC Console pane	2-8
Figure 2.5	Double-click on the file named “test.sav” and click on <input type="button" value="YES"/> in the Warning dialog to execute the test project named “TEST.PRJ”	2-10
Figure 2.6	Graphics plot from “TEST.PRJ”	2-10
Figure 2.7	The UDEC-GIIC main window	2-12
Figure 2.8	The Model Options dialog box	2-14
Figure 2.9	The Model Options dialog with cell space detection logic selected	2-16
Figure 2.10	Project File dialog	2-17
Figure 2.11	New block dialog	2-18
Figure 2.12	Virtual block in <input type="button" value="BLOCK"/> tool	2-18
Figure 2.13	JSet (continuous) dialog used to enter the joint set geometry in the <input type="button" value="JOINTS"/> tool	2-19
Figure 2.14	Continuous joint set created from the JSet (continuous) dialog	2-20
Figure 2.15	Circular tunnel created in the <input type="button" value="JOINTS"/> tool	2-21
Figure 2.16	UDEC jointed rock model with circular tunnel in model-view pane	2-21
Figure 2.17	Zoning of blocks in UDEC model	2-22
Figure 2.18	Property editor dialog to create deformable block materials	2-23
Figure 2.19	Zone material assigned in the <input type="button" value="ZONEMAT"/> tool	2-24
Figure 2.20	Joint Property editor dialog showing the weak joints material and properties	2-25
Figure 2.21	Assignment of joint properties in the <input type="button" value="JOINTMAT"/> tool	2-26
Figure 2.22	<input type="button" value="APPLY"/> tool	2-26
Figure 2.23	Model-view pane with boundary conditions applied	2-27
Figure 2.24	Select gridpoint y-displacement at the tunnel crown to monitor in the <input type="button" value="HISTORY"/> tool	2-28
Figure 2.25	Set gravity settings in the Gravity settings dialog	2-28
Figure 2.26	Solve options dialog from <input type="button" value="RUN"/> stage tool	2-29
Figure 2.27	Save State File dialog	2-30
Figure 2.28	History of maximum unbalanced force	2-30
Figure 2.29	Plot items dialog	2-31
Figure 2.30	Contour plot of $\sigma - yy$ -stresses resulting from gravitational loading	2-32
Figure 2.31	Print plot dialog	2-32
Figure 2.32	Print Setup dialog	2-33
Figure 2.33	UDEC model with tunnel excavated in <input type="button" value="DELETE&ADD"/> tool	2-34
Figure 2.34	Rock with strong joints: y-displacement contours	2-35
Figure 2.35	Creation of two branches in project tree when the <input type="button" value="FOLLOW"/> button is pressed ..	2-36
Figure 2.36	Maximum unbalanced force history	2-36

Figure 2.37	Enter cycle limit in the Cycle dialog	2 - 37
Figure 2.38	Roof block detaches after tunnel excavation in rock with weak joints	2 - 38
Figure 2.39	y-displacement history of gridpoint in roof block after tunnel excavation in rock with weak joints	2 - 38
Figure 2.40	Roof block hits invert of tunnel	2 - 39
Figure 2.41	UDEC Command-line Graphical Interface	2 - 40
Figure 2.42	A simple slope stability example: equilibrium stage (friction angle = 20°)	2 - 43
Figure 2.43	A simple slope stability example: one block sliding (friction angle = 20°)	2 - 44
Figure 2.44	A simple slope stability example: two blocks sliding (friction angle = 11°)	2 - 45
Figure 2.45	Example of a UDEC model (not to scale)	2 - 46
Figure 2.46	UDEC model block divided into two rigid blocks	2 - 50
Figure 2.47	UDEC model block containing two deformable blocks	2 - 51
Figure 2.48	General solution procedure for static analysis	2 - 56
Figure 2.49	Block model with horizontal crack and notch	2 - 59
Figure 2.50	Block model with two continuous joint sets created with block cut joint-set ..	2 - 60
Figure 2.51	Fault intersecting circular tunnel	2 - 62
Figure 2.52	Horseshoe-shaped tunnel with intersecting fault	2 - 63
Figure 2.53	Zoning in a model of a circular tunnel with a 70° fault and a 50° joint set ..	2 - 68
Figure 2.54	Square excavation in jointed rock	2 - 73
Figure 2.55	Maximum unbalanced force history	2 - 74
Figure 2.56	y-displacement history at (0, 2)	2 - 74
Figure 2.57	Roof block falls into opening	2 - 77
Figure 2.58	Roof block stable with one cable	2 - 79
Figure 2.59	Sign convention for positive shear stress components	2 - 81
Figure 2.60	Distortion associated with positive and negative shear strain	2 - 82
Figure 3.1	Spectrum of modeling situations	3 - 2
Figure 3.2	Joint set parameters	3 - 10
Figure 3.3	Four regular joint sets	3 - 12
Figure 3.4	Two discontinuous joint sets	3 - 13
Figure 3.5	Two discontinuous joint sets with discontinuous joint segments deleted (with the JDELETE command)	3 - 13
Figure 3.6	Blocky structure	3 - 14
Figure 3.7	Two hexagonal jointing patterns	3 - 16
Figure 3.8	Block embedded in Voronoi jointed system	3 - 17
Figure 3.9	Block embedded in Voronoi jointed system (iteration = 100)	3 - 18
Figure 3.10	Model with joint-set and voronoi joints	3 - 19
Figure 3.11	Tunnel created after joint set generation	3 - 21
Figure 3.12	Tunnel in jointed rock	3 - 22

Figure 3.13	Specimen with an internal crack	3 - 23
Figure 3.14	Zone dimension used in stiffness calculation	3 - 24
Figure 3.15	Model for Poisson effect in rock with vertical and horizontal jointing	3 - 26
Figure 3.16	Poisson effect for vertically jointed rock ($\nu = 0.3$ for intact rock)	3 - 28
Figure 3.17	Model for Poisson effect in rock with joints dipping at angle θ from the horizontal, and with spacing, S	3 - 28
Figure 3.18	Poisson effect for jointed rock at various joint angles (blocks are rigid)	3 - 29
Figure 3.19	Poisson effect for rock with two equally spaced joint sets, with $\theta = 45^\circ$ (blocks are deformable with $\nu = 0.2$)	3 - 30
Figure 3.20	Rotational displacements induced by forces on a tilted body	3 - 35
Figure 3.21	Small model with two tunnels	3 - 39
Figure 3.22	Large model with two tunnels	3 - 39
Figure 3.23	Numerical experiments on boundary truncation effects for UDEC models containing two tunnels	3 - 44
Figure 3.24	Nonuniform stresses and displacements	3 - 52
Figure 3.25	Uniform stresses and displacements	3 - 53
Figure 3.26	Slip of a confined joint; plot shows shear stress contours	3 - 57
Figure 3.27	Full UDEC model of tunnel region	3 - 60
Figure 3.28	Close-up view of tunnel region	3 - 60
Figure 3.29	Vertical displacement history monitored at ($x = 0, y = 35$)	3 - 62
Figure 3.30	Displacement histories monitored at crown (hist 1) and at wall midpoint (hist 2) of the tunnel	3 - 63
Figure 3.31	Stress-equilibrium after tunnel excavation	3 - 64
Figure 3.32	Unstable blocks identified at 0.2 s of seismic loading	3 - 67
Figure 3.33	Unstable blocks identified at 0.4 s of seismic loading	3 - 67
Figure 3.34	Displacement histories at crown (hist 2) and at wall midpoint (hist 4) for a period of 0.4 s of seismic loading	3 - 68
Figure 3.35	Direct shear test model	3 - 77
Figure 3.36	Average shear stress versus shear displacement – Coulomb slip model	3 - 81
Figure 3.37	Average normal displacement versus shear displacement – Coulomb slip model	3 - 81
Figure 3.38	Average shear stress versus shear displacement – Coulomb slip model with dilation included in the effective friction angle	3 - 83
Figure 3.39	Average normal displacement versus shear displacement – Coulomb slip model with dilation included in the effective friction angle	3 - 83
Figure 3.40	Average shear stress versus shear displacement – Coulomb slip model with peak and residual strength	3 - 84
Figure 3.41	Average normal displacement versus shear displacement – Coulomb slip model with peak and residual strength	3 - 84
Figure 3.42	Average shear stress versus shear displacement – Coulomb joint strength controlled by FISH	3 - 88

Figure 3.43	Average normal displacement versus shear displacement – Coulomb joint strength controlled by <i>FISH</i>	3 - 88
Figure 3.44	Average shear stress versus shear displacement – continuously yielding joint model	3 - 91
Figure 3.45	Average normal displacement versus shear displacement – continuously yielding joint model	3 - 91
Figure 3.46	Average shear stress versus shear displacement for cyclic shear loading using the Coulomb slip model	3 - 95
Figure 3.47	Average normal displacement versus shear displacement for cyclic shear loading using the Coulomb slip model	3 - 96
Figure 3.48	Idealized relation for dilation angle, ψ , from triaxial test results (Vermeer and de Borst 1984)	3 - 101
Figure 3.49	Axial stress versus axial strain for tensile test of tension softening material .	3 - 106
Figure 3.50	Orthogonal strain versus axial strain for tensile test of tension softening material	3 - 106
Figure 3.51	Shear strain contours and velocity vectors in slope model indicating location of failure surface	3 - 124
Figure 3.52	Strength/stress ratios for the Mohr-Coulomb and Hoek-Brown failure criteria	3 - 126
Figure 3.53	A small portion of a jointed rock mass	3 - 128
Figure 4.1	Model constructed in Example 4.9	4 - 9
Figure 4.2	Model constructed in Example 4.13	4 - 14

EXAMPLES

Example 2.1	Dividing a block	2 - 51
Example 2.2	Code to produce model shown in Figure 2.47	2 - 51
Example 2.3	Creating a simple UDEC model	2 - 58
Example 2.4	Generation of two continuous joint sets	2 - 59
Example 2.5	Fault intersecting a circular tunnel	2 - 61
Example 2.6	Horseshoe-shaped excavation with intersecting fault	2 - 62
Example 2.7	Assigning material models and properties	2 - 67
Example 2.8	Applying boundary and initial conditions	2 - 70
Example 2.9	Stepping to initial equilibrium	2 - 71
Example 2.10	Excavate a tunnel and monitor the response	2 - 76
Example 2.11	Stabilize roof block with a cable bolt	2 - 78
Example 3.1	Sawtooth-shaped joint	3 - 7
Example 3.2	Effect of rounding length on crack generation	3 - 7
Example 3.3	Four regular joint sets	3 - 12
Example 3.4	Two discontinuous joint sets	3 - 12
Example 3.5	Blocky structure	3 - 14
Example 3.6	Two hexagonal jointing patterns	3 - 14
Example 3.7	Block embedded in Voronoi jointed system	3 - 16
Example 3.8	Model with joint-set and voronoi joints	3 - 18
Example 3.9	Generation of a tunnel in a jointed rock	3 - 20
Example 3.10	Generation of specimen with an internal crack	3 - 22
Example 3.11	Spin when model is not in equilibrium	3 - 34
Example 3.12	Uplift when material is removed	3 - 35
Example 3.13	Mixing stress and velocity boundary conditions	3 - 36
Example 3.14	Numerical experiments on boundary truncation	3 - 41
Example 3.15	Initial and boundary stresses in equilibrium	3 - 48
Example 3.16	Initial stress state with gravitational gradient	3 - 49
Example 3.17	Initial stress gradient in a nonuniform material	3 - 50
Example 3.18	Nonuniform stress initialized in a model with nonuniform zoning	3 - 51
Example 3.19	Initial stresses following a model change	3 - 54
Example 3.20	Slip of a confined joint	3 - 56
Example 3.21	Stability analysis of an underground excavation – initial model	3 - 58
Example 3.22	Stability analysis of an underground excavation – seismic loading	3 - 64
Example 3.23	Direct shear test with Coulomb slip model	3 - 78
Example 3.24	Direct shear test with joint properties controlled by a FISH function	3 - 85
Example 3.25	Direct shear test with continuously yielding joint model	3 - 88
Example 3.26	Cyclic shear test with Coulomb slip model	3 - 92
Example 3.27	Tension test on tensile-softening material	3 - 103

Example 4.1	Defining a FISH function	4 - 2
Example 4.2	Using a variable	4 - 3
Example 4.3	SET ting variables	4 - 3
Example 4.4	Test your understanding of function and variable names	4 - 4
Example 4.5	Capturing the history of a FISH variable	4 - 4
Example 4.6	FISH functions to calculate bulk and shear moduli	4 - 6
Example 4.7	Using symbolic variables in UDEC input	4 - 7
Example 4.8	Controlled loop in FISH	4 - 7
Example 4.9	Applying a nonlinear initial distribution of moduli	4 - 8
Example 4.10	Splitting lines	4 - 10
Example 4.11	Variable types	4 - 10
Example 4.12	Action of the IF ELSE ENDIF construct	4 - 11
Example 4.13	Automated placing of cable elements	4 - 12
Example 5.1	Benchmark data file – “TIMING.DAT”	5 - 1

