

TABLE OF CONTENTS

1 BLOCK CONSTITUTIVE MODELS

1.1	Introduction	1 - 1
1.2	Constitutive Models in <i>UDEC</i>	1 - 3
1.3	Incremental Formulation	1 - 6
1.3.1	Incremental Equations of the Theory of Plastic Flow	1 - 6
1.3.2	Implementation	1 - 9
1.4	Null Model Group	1 - 10
1.4.1	Null Model	1 - 10
1.4.1.1	block zone cmodel Command and Property Keywords	1 - 10
1.5	Elastic Model Group	1 - 11
1.5.1	Elastic, Isotropic Model	1 - 11
1.5.1.1	block zone cmodel Command and Property Keywords	1 - 12
1.5.2	Elastic, Transversely Isotropic Model	1 - 13
1.5.2.1	block zone cmodel Command and Property Keywords	1 - 18
1.6	Plastic Model Group	1 - 19
1.6.1	Drucker-Prager Model	1 - 21
1.6.1.1	Incremental Elastic Law	1 - 21
1.6.1.2	Yield and Potential Functions	1 - 22
1.6.1.3	Plastic Corrections	1 - 24
1.6.1.4	Implementation Procedure	1 - 27
1.6.1.5	Note on Material Parameters	1 - 27
1.6.1.6	block zone cmodel Command and Property Keywords	1 - 29
1.6.2	Mohr-Coulomb Model	1 - 30
1.6.2.1	Incremental Elastic Law	1 - 30
1.6.2.2	Yield and Potential Functions	1 - 31
1.6.2.3	Plastic Corrections	1 - 34
1.6.2.4	Implementation Procedure	1 - 36
1.6.2.5	Oedometer Test	1 - 36
1.6.2.6	block zone cmodel Command and Property Keywords	1 - 44
1.6.3	Ubiquitous-Joint Model	1 - 45
1.6.3.1	Weak Plane Plastic Corrections	1 - 45
1.6.3.2	Implementation Procedure	1 - 53
1.6.3.3	block zone cmodel Command and Property Keywords	1 - 54
1.6.4	Strain-Hardening/Softening Model	1 - 55
1.6.4.1	Hardening/Softening Parameters	1 - 55
1.6.4.2	User-Defined Functions for Cohesion, Friction, Dilation and Tensile Strength	1 - 57
1.6.4.3	Implementation Procedure	1 - 60

1.6.4.4	block zone cmodel Command and Property Keywords	1 - 61
1.6.5	Bilinear Strain-Hardening/Softening Ubiquitous-Joint Model	1 - 62
1.6.5.1	Failure Criterion and Flow Rule for the Matrix	1 - 62
1.6.5.2	Failure Criterion and Flow Rule for the Weak Plane	1 - 66
1.6.5.3	Large-Strain Update of Orientation	1 - 69
1.6.5.4	Hardening Parameters	1 - 69
1.6.5.5	Implementation Procedure	1 - 71
1.6.5.6	block zone cmodel Command and Property Keywords	1 - 73
1.6.6	Double-Yield Model	1 - 76
1.6.6.1	Incremental Elastic Law	1 - 76
1.6.6.2	Yield and Potential Functions	1 - 78
1.6.6.3	Hardening/Softening Parameters	1 - 79
1.6.6.4	Plastic Corrections	1 - 80
1.6.6.5	Implementation Procedure	1 - 84
1.6.6.6	Choice of Volumetric Properties	1 - 85
1.6.6.7	block zone cmodel Command and Property Keywords	1 - 90
1.6.7	Modified Cam-Clay Model	1 - 91
1.6.7.1	Incremental Elastic Law	1 - 91
1.6.7.2	Yield and Potential Functions	1 - 96
1.6.7.3	Plastic Corrections	1 - 97
1.6.7.4	Hardening/Softening Rule	1 - 99
1.6.7.5	Initial Stress State	1 - 99
1.6.7.6	Overconsolidation Ratio	1 - 99
1.6.7.7	Implementation Procedure	1 - 100
1.6.7.8	Determination of the Input Parameters	1 - 100
1.6.7.9	Oedometer Test	1 - 105
1.6.7.10	block zone cmodel Command and Property Keywords	1 - 113
1.6.8	Hoek-Brown-PAC Model	1 - 114
1.6.8.1	The General Formulation	1 - 114
1.6.8.2	Flow Rules	1 - 116
1.6.8.3	Implementation Procedure	1 - 118
1.6.8.4	Material Softening	1 - 119
1.6.8.5	Triaxial Compression Test	1 - 119
1.6.8.6	block zone cmodel Command and Property Keywords	1 - 130
1.6.9	Hoek-Brown Model	1 - 131
1.6.9.1	Formulation and Implementation	1 - 131
1.6.9.2	Triaxial Compression Test	1 - 133
1.6.9.3	block zone cmodel Command and Property Keywords	1 - 137

1.6.10	Cap-Yield (formerly Cysoil) Model	1 - 139
1.6.10.1	Incremental Elastic Law	1 - 140
1.6.10.2	Yield and Potential Functions	1 - 141
1.6.10.3	Customizing the cap-yield Model	1 - 143
1.6.10.4	Implementation Procedure	1 - 147
1.6.10.5	Isotropic Compression Tests	1 - 147
1.6.10.6	Oedometer Tests	1 - 152
1.6.10.7	Drained Triaxial Tests – Constant Dilation	1 - 156
1.6.10.8	Drained Triaxial Tests – Dilation Hardening	1 - 161
1.6.10.9	block zone cmodel Command and Property Keywords	1 - 165
1.6.11	Cap-yield-simplified (formerly Chsoil) Model	1 - 166
1.6.11.1	Incremental Elastic Law	1 - 166
1.6.11.2	Shear Yield Criterion and Flow Rule	1 - 168
1.6.11.3	Tensile Yield Criterion and Flow Rule	1 - 169
1.6.11.4	Friction Hardening	1 - 169
1.6.11.5	Overconsolidation	1 - 170
1.6.11.6	Shear-Induced Compaction and Dilation	1 - 171
1.6.11.7	Correlation between cap-yield-simplified Properties and Duncan and Chang Properties	1 - 172
1.6.11.8	Calibration of the cap-yield-simplified Model to Triaxial Test Re- sults on Nevada Sand	1 - 173
1.6.11.9	block zone cmodel Command and Property Keywords	1 - 184
1.7	References	1 - 185

2 CONTINUOUSLY YIELDING JOINT MODEL

2.1	Background	2 - 1
2.2	Formulation	2 - 2
2.3	Summary of Continuously Yielding Model Parameters	2 - 5
2.4	Example Applications	2 - 6
2.5	References	2 - 15

3 BARTON-BANDIS JOINT MODEL

3.1	Background	3 - 1
3.2	Joint Normal Behavior	3 - 2
3.3	Joint Shear Behavior	3 - 6
3.4	Input Instructions for the Barton-Bandis Joint Model	3 - 10
3.4.1	UDEC Commands	3 - 10
3.4.2	Program Guide	3 - 19

3.5	Example Problems	3 - 20
3.5.1	Direct Shear Test	3 - 20
3.5.2	Shear Reversal Tests	3 - 24
3.6	References	3 - 35
4	WRITING NEW CONSTITUTIVE MODELS	
4.1	Zones	4 - 1
4.1.1	Methodology	4 - 3
4.1.1.1	Base Class for Constitutive Models	4 - 3
4.1.1.2	Member Functions	4 - 3
4.1.1.3	Registration of Models	4 - 3
4.1.1.4	Information Passed between Model and <i>UDEC</i> during Cycling	4 - 5
4.1.1.5	State Indicators of Zones	4 - 5
4.1.2	Implementation	4 - 8
4.1.2.1	Utility Structures	4 - 8
4.1.2.2	Example Constitutive Model	4 - 9
4.1.2.3	<i>FISH</i> Support for Constitutive Models	4 - 13
4.1.2.4	Loading and Running User-Written Model DLLs	4 - 13
4.1.2.5	Notes on Converting from the Previous Constitutive Model Interface	4 - 14
4.2	Joints	4 - 15
4.2.1	Mohr Coulomb-Slip Joint Model	4 - 15
4.2.2	User-Defined Joint Models	4 - 18
4.2.2.1	Introduction	4 - 18
4.2.2.2	Methodology	4 - 19
4.2.2.3	Implementation	4 - 28
4.3	References	4 - 33

TABLES

Table 1.1	Property groups by failure segment for the bilinear, strain-hardening/softening ubiquitous-joint model	1 - 75
Table 1.2	Cap-yield model properties for isotropic compr. test	1 - 147
Table 1.3	Cap-yield model properties for triaxial test	1 - 156
Table 1.4	Property correlation for input of K_{ref} and G_{ref}	1 - 172
Table 1.5	Property correlation for input of E_{ref} and ν_{ref}	1 - 172
Table 1.6	Calibration results	1 - 175
Table 2.1	Parameters associated with continuously yielding joint model	2 - 5
Table 2.2	Continuously yielding model properties for direct shear tests	2 - 6
Table 3.1	Constants used for calculation of ν_{mi}	3 - 3
Table 3.2	Constants used for calculation of ν_{irr}	3 - 3
Table 3.3	Values used for calculating mobilized roughness $JRC_{mob.}$	3 - 8
Table 3.4	Barton-Bandis model properties for direct shear test	3 - 20
Table 3.5	Barton-Bandis model properties for shear reversal tests	3 - 25
Table 4.1	Failure states and bit assignments	4 - 6
Table 4.2	Failure states and bit assignments	4 - 27

FIGURES

Figure 1.1	Transverse isotropy coordinate axes convention (x_1x_3 -axes are in the plane of isotropy)	1 - 13
Figure 1.2	Drucker-Prager failure criterion in <i>UDEC</i>	1 - 23
Figure 1.3	Drucker-Prager model: domains used in the definition of the flow rule	1 - 24
Figure 1.4	Drucker-Prager and von Mises yield surfaces in principal stress space	1 - 28
Figure 1.5	Mohr-Coulomb and Tresca yield surfaces in principal stress space	1 - 28
Figure 1.6	Mohr-Coulomb failure criterion	1 - 31
Figure 1.7	Mohr-Coulomb model: domains used in the definition of the flow rule	1 - 33
Figure 1.8	Boundary conditions for oedometer test	1 - 37
Figure 1.9	Oedometric test – comparison of numerical and analytical predictions for 10° dilation	1 - 43
Figure 1.10	Oedometric test – comparison of numerical and analytical predictions for 0° dilation	1 - 43
Figure 1.11	A weak plane oriented at an angle θ to the global reference frame	1 - 45
Figure 1.12	Weak-plane failure criterion	1 - 47
Figure 1.13	Ubiquitous-joint model: domains used in the definition of the weak-plane flow rule	1 - 48
Figure 1.14	Example stress-strain curve	1 - 57
Figure 1.15	Variation of cohesion (a) and friction angle (b) with plastic strain	1 - 58
Figure 1.16	Approximation by linear segments	1 - 58
Figure 1.17	Friction (a), cohesion (b), dilation (c) and tensile strength (d) defined by two linear segments	1 - 59
Figure 1.18	<i>UDEC</i> bilinear matrix failure criterion	1 - 63
Figure 1.19	<i>UDEC</i> bilinear joint failure criterion	1 - 66
Figure 1.20	Elastic volumetric loading/unloading paths	1 - 78
Figure 1.21	Isotropic consolidation test	1 - 85
Figure 1.22	Single-element test in which unloading is eleven times stiffer than loading ..	1 - 88
Figure 1.23	Normal consolidation line and unloading-reloading (swelling) line for an iso- tropic compression test	1 - 93
Figure 1.24	Plastic volume change corresponding to an incremental consolidation pressure change	1 - 95
Figure 1.25	Cam-clay failure criterion in <i>UDEC</i>	1 - 96
Figure 1.26	Determination of initial specific volume	1 - 103
Figure 1.27	Boundary conditions for oedometer test	1 - 105
Figure 1.28	Oedometric test – comparison of numerical and analytical values for K_0 ...	1 - 111
Figure 1.29	Oedometric test – history of vertical versus horizontal stresses	1 - 111
Figure 1.30	Oedometric test – history of stresses q versus p	1 - 112
Figure 1.31	Triaxial compression tests – loading conditions	1 - 120

Figure 1.32	Triaxial compression tests – a) Hoek-Brown failure envelope; b) stress-strain plots	1 - 121
Figure 1.33	Triaxial compression tests – a) confining (lateral) strain versus axial strain; b) volumetric strain versus axial strain	1 - 122
Figure 1.34	Triaxial compression test – stress versus axial strain ($\sigma_3/\sigma_{ci} = 0$)	1 - 123
Figure 1.35	Triaxial compression test – lateral strain versus axial strain ($\sigma_3/\sigma_{ci} = 0$)	1 - 123
Figure 1.36	Triaxial compression test – stress versus axial strain ($\sigma_3/\sigma_{ci} = 1.0$)	1 - 124
Figure 1.37	Triaxial compression test – lateral strain versus axial strain ($\sigma_3/\sigma_{ci} = 1.0$)	1 - 124
Figure 1.38	Triaxial compression test – stress versus axial strain ($\sigma_3/\sigma_{ci} = 0$) – modified Hoek-Brown model	1 - 135
Figure 1.39	Triaxial compression test – lateral strain versus axial strain ($\sigma_3/\sigma_{ci} = 0$) – modified Hoek-Brown model	1 - 135
Figure 1.40	Triaxial compression test – stress versus axial strain ($\sigma_3/\sigma_{ci} = 1.0$) – modified Hoek-Brown model	1 - 136
Figure 1.41	Triaxial compression test – lateral strain versus axial strain ($\sigma_3/\sigma_{ci} = 1.0$) – modified Hoek-Brown model	1 - 136
Figure 1.42	Isotropic consolidation test: pressure versus volumetric strain	1 - 143
Figure 1.43	Axial stress (in kN/m^2) versus axial strain for dense, medium and loose sand	1 - 149
Figure 1.44	Bulk modulus (in kN/m^2) versus axial strain for dense, medium and loose sand	1 - 149
Figure 1.45	K_0 versus axial strain for dense, medium and loose sand – $\alpha = 0.5$ (top) and double-yield model (bottom)	1 - 152
Figure 1.46	K_0 versus axial strain for dense, medium and loose sand – $\alpha = 1.0$ (top) and double-yield model (bottom)	1 - 153
Figure 1.47	$ \sigma_1 - \sigma_3 $ (in kN/m^2) versus axial strain for dense, medium and loose sand – constant dilation	1 - 157
Figure 1.48	Volumetric strain versus axial strain for dense, medium and loose sand – constant dilation	1 - 157
Figure 1.49	$ \sigma_1 - \sigma_3 $ (in kN/m^2) versus axial strain for dense, medium and loose sand – constant dilation, cohesion = 100	1 - 159
Figure 1.50	Volumetric strain versus axial strain for dense, medium and loose sand – constant dilation, cohesion = 100	1 - 159
Figure 1.51	$ \sigma_1 - \sigma_3 $ (in kN/m^2) versus axial strain for dense, medium and loose sand – dilation hardening	1 - 162
Figure 1.52	Volumetric strain versus axial strain for dense, medium and loose sand – dilation hardening	1 - 163
Figure 1.53	Deviatoric stress versus mean stress for $D_r = 40\%$ – comparison between laboratory (line) and numerical (cross) results	1 - 175
Figure 1.54	Deviatoric stress versus axial strain (in %) for $D_r = 40\%$ – comparison between laboratory (line) and numerical (cross) results ...	1 - 176

Figure 1.55	Volumetric strain (in %) versus axial strain (in %) for $D_r = 40\%$ – comparison between laboratory (line) and numerical (cross) results	1 - 176
Figure 2.1	Continuously yielding joint model: shear stress-displacement curve and bounding shear strength	2 - 3
Figure 2.2	<i>UDEC</i> model for direct shear test	2 - 7
Figure 2.3	Results of direct shear test using continuously yielding model with initial joint friction at 59.3°	2 - 8
Figure 2.4	Results of direct shear test using continuously yielding model with initial joint friction at 40.1°	2 - 9
Figure 3.1	Parameters used to calculate normal stress during load cycle	3 - 2
Figure 3.2	Parameters used to calculate normal stress during unload cycle	3 - 4
Figure 3.3	Joints numerically cycled to load cycle 4 at start of execution	3 - 5
Figure 3.4	Model for simulating the effects of displacement on shear strength of joints (see Barton 1982 for definition of symbols)	3 - 6
Figure 3.5	<i>UDEC</i> model for direct shear test	3 - 21
Figure 3.6	Average shear stress (MPa) versus shear displacement (mm)	3 - 23
Figure 3.7	Average dilation (mm) versus shear displacement (mm)	3 - 24
Figure 3.8	Average shear stress (MPa) versus shear displacement (mm) for shear reversal with no plateau damage	3 - 28
Figure 3.9	Average dilation (mm) versus shear displacement (mm) for shear reversal with no plateau damage	3 - 29
Figure 3.10	Average shear stress (MPa) versus shear displacement (mm) for shear reversal with plateau damage	3 - 29
Figure 3.11	Average dilation (mm) versus shear displacement (mm) for shear reversal with plateau damage	3 - 30
Figure 3.12	Average shear stress (MPa) versus shear displacement (mm) for partial shear reversal	3 - 34
Figure 3.13	Average dilation (mm) versus shear displacement (mm) for partial shear reversal	3 - 34
Figure 4.1	Mohr-Coulomb slip model (for zero joint cohesion)	4 - 17

EXAMPLES

Example 1.1	Oedometer test on the Mohr-Coulomb model	1 - 40
Example 1.2	Relation between incremental hardening parameter and axial strain increment for an axial compression test	1 - 56
Example 1.3	Piecewise linear definition of softening properties	1 - 59
Example 1.4	Exercising the double-yield model	1 - 86
Example 1.5	Oedometer test on a Cam-clay material	1 - 106
Example 1.6	Triaxial tests on a Hoek-Brown-PAC material	1 - 125
Example 1.7	Isotropic compression tests	1 - 150
Example 1.8	Oedometer tests	1 - 153
Example 1.9	Triaxial tests (constant dilation)	1 - 160
Example 1.10	Triaxial tests (dilation hardening)	1 - 163
Example 1.11	Drained triaxial test at constant mean pressure – $D_r = 40$ – Chsoil model .	1 - 177
Example 2.1	Direct shear test with high peak shear stress	2 - 10
Example 2.2	Direct shear test with low peak shear stress	2 - 12
Example 3.1	Barton-Bandis joint model include file – “BB.FIN”	3 - 19
Example 3.2	Direct shear test with Barton-Bandis joint model	3 - 21
Example 3.3	Shear reversal test with Barton-Bandis joint model	3 - 25
Example 3.4	Partial shear reversal test with Barton-Bandis joint model	3 - 30
Example 4.1	Typical model constructor	4 - 3
Example 4.2	Class specification for the model: file “modelexample.h”	4 - 9
Example 4.3	Constant definition for the example	4 - 10
Example 4.4	Initialization and execution sections of the example model	4 - 10
Example 4.5	Partial class definition for base class, ConstitutiveModel	4 - 20
Example 4.6	Typical model constructor	4 - 23
Example 4.7	Global registration of a model object	4 - 24
Example 4.8	Class specification for model: file “Jmodelexample.h”	4 - 28
Example 4.9	Constant definition for Mohr-Coulomb model	4 - 29
Example 4.10	Initialization and execution sections of the Mohr-Coulomb model	4 - 30

